

BS SPLICE 100 R BLUE

1°

STRUCTURE

CARRIER	CELLULOSE FIBER TISSUE
LINER	WHITE SILICONIZED REPULPABLE PAPER
COLOR	LIGHT BLUE OR CLEAR
ADHESIVE	WATER SOLUBLE ACRYLIC
TOTAL THICKNESS	0.1 U.M. mm (AFERA 4006-ED.9/79)

2°

PHYSICAL PROPERTIES

HEAT RESISTANCE	200 °C (BS INTERNAL METHOD)
REPULPABILITY	FULL (TAPPI UM213-ED. 91)*

*Non-representative results can occur if test guidelines are not followed.

3°

APPLICATION

Double sided repulpable tape with cellulose fiber carrier and with "super easy" siliconized repulpable paper liner.

High cohesion adhesive. Splices without bleeding.

Permanent overlapped splices at rereelers

Temporary splices at sheeters

For medium weight, uncoated and coated papers

4°

RECOMMENDATIONS

- **Storage**
The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.
- **Surface cleaning**
The product shall be applied on sufficiently flat surfaces and with no non-stick coating.
In order to obtain a correct product adhesion level on surfaces, it is indispensable that the surfaces are properly cleaned before the application. It is recommended to use quick-evaporating solvents.
After cleaning make sure that the solvent has completely evaporated, by waiting for a sufficiently long period of time or by drying the surface with a completely dry cloth.
- **Application**
As adhesive tape is pressure-sensitive, it is necessary a proper pressing pressure on the back of the tape, once applied on the surface, to ensure the grip of the adhesive and a full lamination.
- **Measuring tolerances**
The tape cutting width tolerance can vary within a range of ± 2.0 mm.
Different tolerances for specific formats and measures can be available on request
- **Disposal**
It is recommend to dispose the product after use according to the specific regulations of the country it was used in.

Note: All above information are believed to be true and reliable but they are given only for guidance. They do not constitute a warranty or a specification. The characteristics refer to average values, relevant to samples collected from our production. Users must confirm the suitability of the products through their own tests. BiesSse Tape reserve the right to introduce at any moment and without warning those changes that they deem necessary.
Tolerance of Technical Data: $\pm 30\%$