

PAPER			
1°	STRUCTURE		
CARRIER	57 G/SQM IMPREGNATED SEMI-CREPE PAPER		
ADHESIVE	NATURAL RUBBER		
COLOR	YELLOW		
TOTAL THICKNESS	0.12	U.M.	mm
2°	ADHESIVE PROPERTIES		
ADHESION TO STEEL	2.3 N/cm	(± 10%)	
ADHESION TO BACKING	35 N/cm	(± 10%)	
TENSILE STRENGTH	9%	(± 10%)	
3°	PHYSICAL PROPERTIES		
TEMPERATURE RESISTANCE	TO 60 °C		
4°	APPLICATION		
Masking tape suitable for both hot and cold painting for building and automotive industries.			
5°	FEATURES		
Good adhesion on uneven surfaces.			
Maximum conformability			
Clean removal			
Compatible with most popular paints and varnishes			
Tearable by hand			
6°	RECOMMENDATIONS		
<ul style="list-style-type: none"><li><b>Storage</b> For a proper storage of the product we recommend to keep the product in the original package until it is needed and use it within 12 months from delivery. The storage shall be carried out at a room temperature between 15°C and 25°C, and a relative humidity &lt; 65%. Once removed from the packaging, place the product vertically and protect it from dust. Do not expose product and packaging to direct sunlight and heat sources.</li><li><b>Surface cleaning</b> The product shall be applied on sufficiently flat surfaces and with no non-stick coating. In order to obtain a correct product adhesion level on surfaces, it is indispensable that the surfaces are properly cleaned before the application. It is recommended to use quick-evaporating solvents. After cleaning make sure that the solvent has completely evaporated, by waiting for a sufficiently long period of time or by drying the surface with a completely dry cloth.</li><li><b>Application</b> As adhesive tape is pressure-sensitive, it is necessary a proper pressing pressure on the back of the tape, once applied on the surface, to ensure the grip of the adhesive and a full lamination.</li><li><b>Measuring tolerances</b> The tape cutting width tolerance can vary within a range of ±2.0 mm. Different tolerances for specific formats and measures can be available on request</li><li><b>Disposal</b> It is recommend to dispose the product after use according to the specific regulations of the country it was used in.</li></ul>			
Note: All above information are believed to be true and reliable but they are given only for guidance. They do not constitute a warranty or a specification. The characteristics refer to average values, relevant to samples collected from our production. Users must confirm the suitability of the products through their own tests. BiesSse Tape reserve the right to introduce at any moment and without warning those changes that they deem necessary. Tolerance of Technical Data: + 30%			